

VUEROID

intelligent • innovative • insightful



VUEROID



D20-Q2

PRODUCT SPECIFICATIONS

CAMERA

CIS
RESOLUTION
VIEW ANGLE

Front / Rear : SONY Starvis 5M (IMX335)
Front / Rear : 2560 x 1440 @ 30fps
Front / Rear : (D)145° x (H)115° x (V)62°

MEMORY CARD

Micro SD Card (Support up to 256GB)

GPS

Built-in Antenna

WI-FI

External Wi-Fi (Usb Dongle)

LED INDICATORS

Front : Security & Status LED / Rear : Security LED

G-SENSOR

3-Axis Acceleration Sensor, +2g / -2g

SPEAKER

Built-in Speaker (Voice Guide)

MICROPHONE

Built-in Microphone

VIDEO CODEC

H.264 High Profile

RECORDING MODE

Normal / Event / Manual / Parking (Motion & Time-Lapse)

DIMENSIONS

Front : 107.8mm x 42.6mm x 75.4mm

Rear : 52mm x 29mm x 42mm

Front : 107.5g / Rear : 28g

WEIGHT

DC 12V ~ 24V

POWER INPUT

Max. 5.4W @ 12V

POWER CONSUMPTION

-20°C ~ 70°C (-4°F ~ 158°F)

OPERATING TEMP.

Approximate 70°C (158°F) / Battery Discharge Prevention

HIGH TEMP. CUT-OFF



2-Channel



CMOS
Image Sensor



ADAS



Safety
Camera Alert



Night Vision



FOV 145°



Prevent
Discharge



Time Lapse



Format Free



Built-in GPS

VUEROID



D20-F2

PRODUCT SPECIFICATIONS

CAMERA

CIS
RESOLUTION
VIEW ANGLE

Front / Rear : SONY Starvis 2M (IMX307)
Front / Rear : 1920 x 1080 @ 30fps
Front / Rear : (D)145° x (H)116° x (V)90°

MEMORY CARD

Micro SD Card (Support up to 256GB)

GPS

Built-in Antenna

WI-FI

External Wi-Fi (USB Dongle)

LED INDICATORS

Front : Security & Status LED / Rear : Security LED

G-SENSOR

3-Axis Acceleration Sensor, +2g / -2g

SPEAKER

Built-in Speaker (Voice Guide)

MICROPHONE

Built-in Microphone

VIDEO CODEC

H.264 High Profile

RECORDING MODE

Normal / Event / Manual / Parking (Motion & Time-Lapse)

DIMENSIONS

Front : 107.8mm x 42.6mm x 75.4mm

Rear : 52mm x 29mm x 42mm

Front : 107.5g / Rear : 28g

WEIGHT

DC 12V ~ 24V

POWER INPUT

Max. 5.4W @ 12V

POWER CONSUMPTION

-20°C ~ 70°C (-4°F ~ 158°F)

OPERATING TEMP.

Approximate 70°C (158°F) / Battery Discharge Prevention

HIGH TEMP. CUT-OFF

FHD

2-Channel

SONY
STARVIS

CMOS
Image Sensor



ADAS



Safety
Camera Alert



Night Vision



FOV 145°



Prevent
Discharge



Time Lapse



Format Free



Built-in GPS

VUEROID



Zero

PRODUCT SPECIFICATIONS

CAMERA

CIS
RESOLUTION

Front : SONY Starvis 2M (IMX307) - 1920 x 1080 @ 30fps
Rear : CMOS Sensor - 1920 x 1080 @ 30fps

VIEW ANGLE

Front : (D)145° x (H)116° x (V)60°
Rear : (D)128° x (H)105° x (V)55°

MEMORY CARD

Micro SD Card (Support up to 256GB)

GPS

N/A

WI-FI

External Wi-Fi (USB Dongle)

LED INDICATORS

Front : Security & Status LED / Rear : Security LED

G-SENSOR

3-Axis Acceleration Sensor, +2g / -2g

SPEAKER

Built-in Speaker (Voice Guide)

MICROPHONE

Built-in Microphone

VIDEO CODEC

H.264 High Profile

RECORDING MODE

Normal / Event / Manual / Parking (Motion & Time-Lapse)

DIMENSIONS

Front : 112mm x 72mm x 35mm

Rear : 52mm x 29mm x 42mm

WEIGHT

Front : 107.5g / Rear : 28g

POWER INPUT

DC 12V ~ 24V

POWER CONSUMPTION

Max. 4W @ 12V

OPERATING TEMP.

-20°C ~ 70°C (-4°F ~ 158°F)

HIGH TEMP. CUT-OFF

Approximate 70°C (158°F) / Battery Discharge Prevention

1080P
FHD

2-Channel

SONY
STARVIS

CMOS
Image Sensor



Safety
Camera Alert



HDR



Night Vision



FOV 145°



Prevent
Discharge



Time Lapse



Format Free